


# RADIO RECEIVER ASSY REPLACEMENT

6715R-01

## HINT:


- COMPONENTS: See page 67-2
- Installation is in the reverse order of removal.

### 1. REMOVE INSTRUMENT CLUSTER FINISH PANEL SUB-ASSY CENTER (SEE PAGE 71-10)




### 2. REMOVE INTEGRATION CONTROL & PANEL ASSY

- Remove the 6 bolts.
- Disconnect the connectors and remove the integration control & panel assy.




### 3. REMOVE RADIO BRACKET NO.1 (W/O EMV & NAVIGATION SYSTEM)

- Remove the 4 bolts, 2 screws and radio bracket No. 1.




### 4. REMOVE MULTI-DISPLAY CONTROLLER BRACKET A (W/ EMV & NAVIGATION SYSTEM)

- Remove the 7 screws and multi-display controller bracket A.



### 5. REMOVE RADIO BRACKET NO.2 (W/O EMV & NAVIGATION SYSTEM)

- Remove the 4 bolts, 2 screws and radio bracket No. 2.



- 6. REMOVE MULTI-DISPLAY CONTROLLER BRACKET B (W/ EMV & NAVIGATION SYSTEM)**
- (a) Remove the 7 screws and multi-display controller bracket B.

**7. REMOVE RADIO RECEIVER ASSY**