


REAR SPOILER REPLACEMENT

1. REMOVE BACK WINDOW PANEL TRIM UPPER (See page 75-20)



2. REMOVE REAR SPOILER

- Remove the 2 bolts and nut.
- Using a heat light, heat the body and rear spoiler to 40 to 60°C (104 to 140°F).

NOTICE:

Do not heat the rear spoiler excessively.

- Tie both piano wire ends to a wooden block or a similar object.
- Scrape the adhesive tape off by pulling the piano wire.

NOTICE:

- If reusing the rear spoiler, take care not to damage the rear spoiler.
- Do not damage the body.

- Remove the rear spoiler.

3. INSTALL REAR SPOILER

- Using a heat light, heat the body and rear spoiler surface to 40 to 60°C (104 to 140°F).

NOTICE:

Do not heat the body and rear spoiler excessively.

- Remove the adhesive tape from the body.
- Wipe off the stains with cleaner.
- If reusing the rear spoiler:
Clean the rear spoiler .
 - Using a heat light, heat the body and rear spoiler to 20 to 30°C (68 to 86°F).

NOTICE:

Do not heat the body and rear spoiler excessively.

- Remove the adhesive tape from the rear spoiler.
- Wipe off the stains with cleaner.

- Apply new adhesive tape to the rear spoiler as shown in the illustration.


- Using a heat light, heat the body and rear spoiler.

Heating temperature:

Body	40 to 60°C (104 to 140°F)
Moulding	20 to 30°C (68 to 86°F)

NOTICE:

Do not heat the body and rear spoiler excessively.



- (f) Lift the rear spoiler and release the release sheet from the surface of the rear spoiler.

NOTICE:

- **When the rear spoiler release sheet is removed, take care that no dirt or no dust can get onto the uncoated area.**
- **Do not apply excessive force onto the rear spoiler but steady pressure with your thumbs.**