

## TORQUE SPECIFICATION

Part Tightened	N·m	kgf·cm	ft·lbf
Intermediate shaft x Center support bearing assy No. 1 (front)			
1st	182	1,850	134
Loosen nut			
2nd	69	700	51
Intermediate shaft x Center support bearing assy No. 1 (rear)			
1st	182	1,850	134
Loosen nut			
2nd	69	700	51
Propeller shaft assy x Front flange	74	750	54
Propeller shaft assy rear x Rear differential	74	750	54
Intermediate shaft rear flange x Propeller shaft assy rear	29	296	21
Center support bearing assy No. 1 (front) x Body	37	375	27
Center support bearing assy No. 1 (rear) x Body	37	375	27
Front wheel set nut	103	1,050	76
Lower ball joint x Lower suspension arm	127	1,300	94
Tie rod end x Steering knuckle	49	500	36
Axle hub x Front drive shaft	294	3,000	217
Front disc brake caliper assy x Steering knuckle	104	1,060	77
Front drive shaft center bearing set bolt 2WD	32	330	24
Front speed sensor set bolt	8.0	82	71 in.·lbf
Flexible hose and speed sensor wire harness x Shock absorber	19	192	14
Rear wheel set nut	103	1,050	76
Speed sensor x Rear axle carrier 4WD	8.0	82	71 in.·lbf
Axle hub x Rear drive shaft 4WD	294	3,000	217
Rear axle carrier sub-assy x Rear disc brake caliper	78	800	58
Front stabilizer Link assy x Shock absorber	74	755	55
Shock absorber x Steering knuckle	230	2,350	170
Front axle carrier x Lower ball joint	123	1,250	91
Rear axle carrier sub-assy x Rear axle hub & bearing	75	765	55
Transfer extension housing x Transfer dynamic damper	26	260	19
Rear shock absorber x Flexible hose	19	192	14
Rear axle carrier sub-assy x Strut rod assy rear	80	816	59
Rear axle carrier sub-assy x Rear suspension arm assy No.1 LH	112	1,140	83
Rear axle carrier sub-assy x Rear suspension arm assy No.2 LH	112	1,140	83
Disc brake dust cover front x Steering knuckle	8.3	85	74 in.·lbf
Rear shock absorber x Rear axle carrier	180	1,840	133